

CEL-FI™ QUATRA 2000

3G / 4G / LTE



In-building Cellular Solution

Cel-Fi QUATRA 2000 is a scalable in-building cellular solution that is both a cost-efficient and easy-to-deploy solution, delivering high-quality signal in venues up to 200,000 square feet (20,000 square meters). It is a hybrid solution that combines the best of active DAS and Smart Booster technologies. The Cel-Fi QUATRA 2000 operates by capturing the signal from the outside macro networks, boosting them, and relaying their signals indoor from the coverage units.



Benefits:

- **Lowest Solution Costs per ft²**
- **Scalable Coverage for 200,000 ft² (20,000 m²), and Beyond**
- **Easiest-to-Deploy with Signal Quality Maximized by AntennaBoost**
- **Remote Monitoring and Management via Cel-Fi WAVE Platform**

System Features

Enterprise-class, carrier-grade, small footprint active DAS

RF inputs for external off-air donor antenna (A11-V14-100)
 Network Unit (NU) (Head End) attaches to Coverage Unit (CU) (Remote Unit) via Cat 5e cable
 A single NU and up to four (4) CUs may be attached (hub and spoke architecture) in a Cel-Fi QUATRA 2000 system
 Multiple Cel-Fi QUATRA 2000 systems may be deployed to increase coverage footprint
 Up to 325 ft (100 m) range from NU to CU
 Cel-Fi QUATRA Range Extender (QRE) (optional) may be used to increase NU-to-CU distance to 650 ft (200 m)
 Remote Management through Nextivity's Cel-Fi WAVE cloud platform
 Easiest installation in its class
 Glanceable LED User Interface (UI)
 Supporting smart phone application (QMT)
 Mounting hardware included

Wireless Features

Supports up to two bands simultaneously from two operators

3G/4G/LTE support (CDMA / WCDMA / HSPA+ / LTE)
 Supports FDD
 Up to 100dB system gain per band (in Off-Air mode)
 Peaceful coexistence with adjacent Wi-Fi (2.4 GHz & 5 GHz), femtocells, and cellular devices
 Advanced digital echo-cancellation (>30dB) and channel select filtering algorithms
 Active management of the cellular link between the Base Station and user devices
 Automatic Gain Control (AGC) based on fast real-time echo-cancellation
 Linear RF front end
 Adaptive signal equalization
 Uses Nextivity's 3rd-generation "ARES" chipset

Mobile Network and Network Protection Features

Dual-carrier combinations available: AT&T and Verizon; Sprint (FDD) and T-Mobile
 Integration, handover, and handoff with the macro network
 Supports multiple channels with bandwidths of 3.84/5/10/15/20 MHz per channel
 Works with any user equipment (UE) for the configured networks (no whitelist/blacklist)
 Up to 75 MHz system relay bandwidth
 Support for 3GPP Release 10 features
 Provider-specific operation: Cel-Fi QUATRA 2000 distributes and boosts service only for the Operator PLMNIDs for which the device is authorized and configured
 Secure and ciphered provisioning
 System intelligence accurately establishes proper safe uplink power in real time
 Uplink Muting Mode automatically shuts down uplink cellular transmissions when no active user equipment is detected

Benefits

Easiest to deploy Active DAS Hybrid
 Distribute and boost cellular coverage indoors
 3G and 4G support, Voice and Data, network safe
 Coverage footprint provided via Power over Ethernet (PoE); no requirement for additional power source at CU (RU)

Donor Signal

Simplest Installation: NU (Head End) and CU (RU) connect with Cat 5e-rated (or better) cable
Scalable architecture allows multiple Cel-Fi QUATRA 2000 systems to be deployed in the same environment for larger footprint
LED cues provides visual feedback for ease of setup and status
Works with any subscriber device from the configured carrier
QMT (QUATRA Management Tool) smartphone app further simplifies installation
System management locally or from the cloud through the Cel-Fi WAVE platform
Wall and ceiling mounting options

Wireless Benefits

Clear and reliable cellular connections within coverage area up to 50,000 ft² (5000 m²) per system, and beyond
Highest gain (100dB) provides best coverage footprint on location
Advanced Echo-Cancelation allows Cel-Fi QUATRA 2000 to transmit more power without feedback interference
Subscriber devices require less transmit power for improved battery life
Linearity eliminates IMD desense issues
Dynamic gain control ensures maximum gain—best coverage—at all times in ever changing RF environments, without user intervention
Nextivity purpose-built, high-performance, six core ASIC processor, provides best performance at lowest cost

Mobile Network Benefits


Flexibly deploy in LTE, VoLTE, LTE-Advanced, CDMA and WCDMA networks, with multiple cellular bands, simultaneously
Automatically adjusts channel bandwidths from 3.84 MHz to 20 MHz
Sufficient relay bandwidth (75 MHz) to support SISO in multiple bands
Off-load the macro network, or use to improve macro capacity and building propagation/penetration
Cel-Fi QUATRA 2000 system improves users' cellular experience while remaining invisible to networks and UEs: no gateways or third-party software needed
UE control is transparent and remains centralized in the network core (no gateways or third-party software)

Variants

Model Number	Bands Supported	Carrier Configurations Available
Q34-4/5/12/13/25	4, 5, 12, 13, 25	AT&T & Verizon T-Mobile & Sprint

QUATRA Range Extender (QRE)

#Q34-E1000




The Cel-Fi QUATRA Range Extender is a Power over Ethernet (PoE) device that allows Cel-Fi QUATRA 2000 Network Unit (NU) to Coverage Unit (CU) interconnect cable lengths up to 650 ft (200 m). Plug and Play installation.

Power over Ethernet (PoE)
Extends NU to CU cable to 650 ft (200 m)
Supports Cel-Fi QUATRA 2000 proprietary protocols
Intuitive LED interface
Note: Will not support other (non Cel-Fi QUATRA 2000) PoE devices

Indoor Omni Antenna


#A11-V43-100



The Wideband Indoor Dome Server Antenna receives and transmits signal in a 360° pattern
Compatible with the 698 – 2700 MHz frequency ranges that include 3G and 4G signals
Omni-Directional
SMA Male connector

Wideband Omni Donor

#A11-V14-100



The Wideband Omni-Directional MIMO Antenna is perfect for use as an outdoor cellular donor signal source
698 – 2700 MHz
N-type connector

Power
(Network Unit only)

54 VDC @ 2.22 Amp via external supply (51.3 to 56.7 VDC tolerance)
External supply: 100 to 240 VAC, 47 – 63 Hz
Power consumption less than 120W max
Network Unit provides power to Coverage Units over Cat 5e (PoE)

Environmental

Operating temperature: 0° to 40°C
Storage temperature: -25° to 60°C
Convection Cooling
Relative humidity: 0% to 95%, noncondensing
RoHS II 2011/65/EU
IP20

Installation

Mounting hardware included
NU may be wall mounted (solid or hollow)
CUs may be wall or ceiling mounted
1 NU supports 1 to 4 CUs
iBwave VEX files available

Radio Performance
(check product version
for specific band support)

Band	Downlink	Uplink	Boost
4	2110-2155 MHz	1710-1755 MHz	Up to 20 MHz contiguous boost BW, HSPA or LTE MIMO
5	869-894 MHz	824-849 MHz	Up to 15 MHz contiguous boost BW, HSPA or LTE SISO
12	729-746 MHz	699-716 MHz	Up to 10 MHz contiguous boost BW, LTE MIMO
13	746-756 MHz	777-787 MHz	Up to 10 MHz contiguous boost BW, LTE MIMO
25	1930-1995 MHz	1850-1915 MHz	Up to 20 MHz contiguous boost BW, HSPA or LTE SISO

Total boost all-channel bandwidth 75 MHz
 DL Maximum NU in-band donor level -40dBm
 DL Maximum NU survival donor level 30dBm
 UL Maximum CU donor level -20dBm
 Maximum UL power 24dBm EIRP bands 4, 25
 Maximum UL power 20dBm EIRP bands 5, 12, 13,
 Maximum DL power 10dBm per 5 MHz EIRP all bands
 LTE 5/10/15/20 MHz and WCDMA 3.84/5MHz bandwidths

Physical Specifications

Network Unit	Coverage Unit
264x185x62mm	225x185x37mm
1.2 kg (40.8 oz.)	0.83 kg (29.2 oz.)

Connections

4x CU RJ45 Proprietary Gigabit link
 100m max CU cable length Cat 5e
 200m max CU cable length with Cel-Fi QUATRA Range Extender (Cat 5e or Cat 6)
 PoE IEEE 802.3at
 RJ45 LAN management port (10/100 Fast Ethernet)
 RJ45 LAN management output port (10/100 Fast Ethernet)
 2x External RF Input (QMA Female 50 ohm)

Compliance
(check individual product version
for specific regional compliance)

3GPP TS 25.143 Rel.10
 3GPP TS 36.143 Rel.10
 FCC Part 15, 20, 22, 24, 27
 ISED Canada
 UL 62368-1/CSA C27.2
 Bluetooth BQB
 Note: Certifications are regional; not all products need or have the same certifications. Please check the specific model number to determine exactly which certifications it has.

System Management
(Software)

Cel-Fi QUATRA Management Tool (QMT)
 Cel-Fi WAVE cloud portal
 Cel-Fi WAVE Remote Management:
 • Status (List and Map) • Settings
 • Commissioning • Reporting
 • Diagnostics • Alarms & Notifications
 • Software Updates

Patents & Design

Cel-Fi QUATRA 2000 products are covered by Nextivity, Inc., patents and patents pending. Designed by Nextivity, Inc. in San Diego, California, USA. Please refer to cel-fi.com for details.
 Specifications subject to change without notice.