



230V MICRO DATA CENTER SPECIFICATIONS

Updated July 2019

Base Configurations

Voltage	Form Factor	Usable Rack Space	Output Power Capacity	UPS Type	Applications	Page
230V	Wall-Mount	9U to 15U	1.5 kVA to 3 kVA	Line-Interactive	A B D E F G I	1 – 2
230V	Compact Floor-Standing	15U to 21U	1.5 kVA to 3 kVA	Line-Interactive	A B C E F G I	3
230V	Full-Size Floor-Standing	30U to 40U	3 kVA to 10 kVA (N+N)	On-Line	A B C E F G H I	4 – 6

Common Micro Data Center Applications					
A	Reduce Network Latency	D	Minimize Space Requirements	G	Protect Important Data
B	Simplify Configuration	E	Standardize Deployments	H	Protect Mission-Critical Data
C	Accelerate Installation	F	Support High Availability	I	Minimize Support Requirements

Wall-Mount Micro Data Centers (230V)

Model Summary	230V Wall-Mount • 9U • 1.5 kVA	230V Wall-Mount • 12U • 1.5 kVA
Model (Validated Kit)	MDK2W09UPX00000	MDK2W12UPX00000
Model (Assembled/Tested)	Not Available	Not Available
Output Power Capacity	1.5 kVA/1.35 kW/5.9A Max	1.5 kVA/1.35 kW/5.9A Max
Rack Space	12U Total; 9U Usable	15U Total; 12U Usable
Weight Capacity	90 kg Total; 47 kg Usable	90 kg Total; 36 kg Usable
Maximum Device Depth	419 mm	521 mm
Site Power Requirements	230V, 13/16A, 50/60 Hz	230V, 13/16A, 50/60 Hz
Site Outlet Required	BS 1363 (Standard) or CEE 7/7 "Schuko" (Optional)	BS 1363 (Standard) or CEE 7/7 "Schuko" (Optional)
UPS Type	Line-Interactive with Sine Wave Output	Line-Interactive with Sine Wave Output
Runtime (50%/100% Load)	14/4.9 min. (Expandable with 1.2 kW Limit)	14/4.9 min. (Expandable with 1.2 kW Limit)
High-Availability Features	Automatic Voltage Regulation (AVR); Battery Backup; Hot-Swappable Batteries	Automatic Voltage Regulation (AVR); Battery Backup; Hot-Swappable Batteries
PDU Type	Basic	Basic
Usable Outlets (UPS + PDU)	(19) C13, (2) C19	(19) C13, (2) C19
Dimensions (Assembled)	637 x 600 x 449 mm	770 x 600 x 549 mm
Weight (Assembled)	44 kg	55 kg
Limited Warranty	2 Years (Components Keep Longer Warranties); Extended Warranties Available	2 Years (Components Keep Longer Warranties); Extended Warranties Available

Included Hardware and Usable AC Outlets		
Rack Enclosure	SRW12U (Wall-Mount Rack)	SRW15US (Wall-Mount Rack)
UPS System	SMX1500XLRT2U with (7) C13; UK Input Cord with BS 1363 Plug (P056-006-10A)	SMX1500XLRT2U with (7) C13; UK Input Cord with BS 1363 Plug (P056-006-10A)
UPS Network Card	WEBCARDLX	WEBCARDLX
Environmental Sensor	E2MTHDI (Temperature/Humidity/Digital Inputs)	E2MTHDI (Temperature/Humidity/Digital Inputs)
Standard PDU	PDU12IEC with (12) C13, (2) C19; 1U; P047-004 Input Cord	PDU12IEC with (12) C13, (2) C19; 1U; P047-004 Input Cord

Optional Accessories, Sold Separately (Visit www.tripplite.com to see the full selection.)		
Switched PDU*	PDUMH15HVNET with (8) C13; 1U	PDUMH15HVNET with (8) C13; 1U
External Battery Packs for Extended Runtime (50%/100% Load)	59/23 min. with BP36V15-2U (Limit 1); 85/34 min. with BP36V27-2US; 177/73 min. with BP36V42-3U	59/23 min. with BP36V15-2U (Limit 1); 85/34 min. with BP36V27-2US; 177/73 min. with BP36V42-3U
Cooling	Not Available	Not Available
KVM Switch	B022-U08-IP	B022-U08-IP
Console Server	B093-004-2E4U	B093-004-2E4U
Door Monitoring Kit	SRSWITCH	SRSWITCH
Airflow Management	SR1UPANEL10 and/or SR1UBRUSH	SR1UPANEL10 and/or SR1UBRUSH
Cable Managers	40+ Horizontal, Vertical and External Cable Management Options at tripplite.com	
Power Cords	French/German UPS Input Cord with CEE 7/7 "Schuko" Plug (P054-006); Match Others to IT Equipment; 250+ Power Cord Options at tripplite.com	
Network Cables	Match to IT Equipment; 1,000+ Copper and Fiber Network Cable Options at tripplite.com	
Patch Panels	60+ Copper and Fiber Patch Panel Options at tripplite.com	
Additional Sensors	E2MT (Up to 3 Sensors Total per WEBCARDLX to Monitor Top/Middle/Bottom Temperature)	

* Replaces standard PDU.

Heavy-Duty Wall-Mount Micro Data Centers (230V)

Model Summary	230V Heavy-Duty Wall-Mount • 9U • 1.5 kVA	230V Heavy-Duty Wall-Mount • 15U • 3 kVA
Model (Validated Kit)	MDK2W09UPX00001	MDK2W15UPX00000
Model (Assembled/Tested)	Not Available	Not Available
Output Power Capacity	1.5 kVA/1.35 kW/5.9A Max	3 kVA/2.7 kW/11.7A Max
Rack Space	12U Total; 9U Usable	18U Total; 15U Usable
Weight Capacity	226 kg Total; 156 kg Usable	226 kg Total; 137 kg Usable
Maximum Device Depth	826 mm	826 mm
Site Power Requirements	230V, 13/16A, 50/60 Hz	230V, 13/16A, 50/60 Hz
Site Outlet Required	BS 1363 (Standard) or CEE 7/7 "Schuko" (Optional)	BS 1363 (Standard) or CEE 7/7 "Schuko" (Optional)
UPS Type	Line-Interactive with Sine Wave Output	Line-Interactive with Sine Wave Output
Runtime (50%/100% Load)	14/4.9 min. (Expandable with 1.2 kW Limit)	11/3.9 min. (Expandable)
High-Availability Features	Automatic Voltage Regulation (AVR); Battery Backup; Hot-Swappable Batteries	Automatic Voltage Regulation (AVR); Battery Backup; Hot-Swappable Batteries
PDU Type	Basic	Metered
Usable Outlets (UPS + PDU)	(19) C13, (2) C19	(16) C13, (2) C19
Dimensions (Assembled)	672 x 920 x 629 mm	939 x 920 x 629 mm
Weight (Assembled)	71 kg	90 kg
Limited Warranty	2 Years (Components Keep Longer Warranties); Extended Warranties Available	2 Years (Components Keep Longer Warranties); Extended Warranties Available
Included Hardware and Usable AC Outlets		
Rack Enclosure	SRW12UHD (Heavy-Duty Wall-Mount Rack)	SRW18UHD (Heavy-Duty Wall-Mount Rack)
UPS System	SMX1500XLR2U with (7) C13; UK Input Cord with BS 1363 Plug (P056-006-10A)	SMX3000XLR2UA with (8) C13; UK Input Cord with BS 1363 Plug (P052-008)
UPS Network Card	WEBCARDLX	WEBCARDLX
Environmental Sensor	E2MTHDI (Temperature/Humidity/Digital Inputs)	E2MTHDI (Temperature/Humidity/Digital Inputs)
Standard PDU	PDU12IEC with (12) C13, (2) C19; 1U; P047-004 Input Cord	PDUMH20HV with (8) C13, (2) C19; 1U
Optional Accessories, Sold Separately (Visit www.tripplite.com to see the full selection.)		
Switched PDU*	PDUMH15HVNET with (8) C13; 1U	PDUMH20HVNET with (8) C13; 1U
External Battery Packs for Extended Runtime (50%/100% Load)	59/23 min. with BP36V15-2U (Limit 1); 85/34 min. with BP36V27-2US ; 177/73 min. with BP36V42-3U	30/11 min. with BP48V24-2U (Limit 1); 43/16 min. with BP48V27-2US ; 67/26 min. with BP48V60RT-3U
Cooling	Not Available	Not Available
KVM Switch	B022-U08-IP	B022-U08-IP
Console Server	B093-004-2E4U	B093-004-2E4U
Door Monitoring Kit	SRSWITCH (Monitors Front/Rear Doors)	SRSWITCH (Monitors Front/Rear Doors)
Airflow Management	SR1UPANEL10 and/or SR1UBRUSH	SR1UPANEL10 and/or SR1UBRUSH
Cable Managers	40+ Horizontal, Vertical and External Cable Management Options at tripplite.com	
Power Cords	French/German UPS Input Cord with CEE 7/7 "Schuko" Plug (P054-006); Match Others to IT Equipment; 250+ Power Cord Options at tripplite.com	French/German UPS Input Cord with CEE 7/7 "Schuko" Plug (P050-008); Match Others to IT Equipment; 250+ Power Cord Options at tripplite.com
Network Cables	Match to IT Equipment; 1,000+ Copper and Fiber Network Cable Options at tripplite.com	
Patch Panels	60+ Copper and Fiber Patch Panel Options at tripplite.com	
Additional Sensors	E2MT (Up to 3 Sensors Total per WEBCARDLX to Monitor Top/Middle/Bottom Temperature)	

* Replaces standard PDU.

Compact Floor-Standing Micro Data Centers (230V)

Model Summary	230V • 15U • 1.5 kVA	230V • 21U • 3 kVA
Model (Validated Kit)	MDK2F15UPX00000	MDK2F21UPX00000
Model (Assembled/Tested)	MDA2F15UPX00000	MDA2F21UPX00000
Output Power Capacity	1.5 kVA/1.35 kW/5.9A Max	3 kVA/2.7 kW/11.7A Max
Rack Space	18U Total; 15U Usable	24U Total; 21U Usable
Weight Capacity	453 kg Total; 382 kg Usable	453 kg Total; 363 kg Usable
Maximum Device Depth	826 mm	826 mm
Site Power Requirements	230V, 13/16A, 50/60 Hz	230V, 13/16A, 50/60 Hz
Site Outlet Required	BS 1363 (Standard) or CEE 7/7 "Schuko" (Optional)	BS 1363 (Standard) or CEE 7/7 "Schuko" (Optional)
UPS Type	Line-Interactive with Sine Wave Output	Line-Interactive with Sine Wave Output
Runtime (50%/100% Load)	14/4.9 min. (Expandable with 1.2 kW Limit)	11/3.9 min. (Expandable)
High-Availability Features	Automatic Voltage Regulation (AVR); Battery Backup; Hot-Swappable Batteries	Automatic Voltage Regulation (AVR); Battery Backup; Hot-Swappable Batteries
PDU Type	Basic	Metered
Usable Outlets (UPS + PDU)	(19) C13, (2) C19	(16) C13, (2) C19
Dimensions (Assembled)	904 x 600 x 851 mm	1158 x 600 x 851 mm
Weight (Assembled)	72 kg	91 kg
Limited Warranty	2 Years (Components Keep Longer Warranties); Extended Warranties Available	2 Years (Components Keep Longer Warranties); Extended Warranties Available
Included Hardware and Usable AC Outlets		
Rack Enclosure	SR18UB (Compact Rack; Standard Width)	SR24UB (Compact Rack; Standard Width)
UPS System	SMX1500XLRT2U with (7) C13; UK Input Cord with BS 1363 Plug (P056-006-10A)	SMX3000XLRT2UA with (8) C13; UK Input Cord with BS 1363 Plug (P052-008)
UPS Network Card	WEBCARDLX	WEBCARDLX
Environmental Sensor	E2MTHDI (Temperature/Humidity/Digital Inputs)	E2MTHDI (Temperature/Humidity/Digital Inputs)
Standard PDU	PDU12IEC with (12) C13, (2) C19; 1U; P047-004 Input Cord	PDUMH20HV with (8) C13, (2) C19; 1U
Optional Accessories, Sold Separately (Visit www.tripplite.com to see the full selection.)		
Switched PDU*	PDUMH15HVNET with (8) C13; 1U	PDUMH20HVNET with (8) C13; 1U
External Battery Packs for Extended Runtime (50%/100% Load)	59/23 min. with BP36V15-2U (Limit 1); 85/34 min. with BP36V27-2US ; 177/73 min. with BP36V42-3U	30/11 min. with BP48V24-2U (Limit 1); 43/16 min. with BP48V27-2US ; 67/26 min. with BP48V60RT-3U
Cooling	SRXCOOL12KB (3.5 kW; Portable; BS 1363) or SRXCOOL12K (3.5 kW; Portable; CEE 7/7 "Schuko")	SRXCOOL12KB (3.5 kW; Portable; BS 1363) or SRXCOOL12K (3.5 kW; Portable; CEE 7/7 "Schuko")
KVM Switch	B022-U16-IP ; B020-U16-19-IP (With LCD Console)	B022-U16-IP ; B020-U16-19-IP (With LCD Console)
Console Server	B093-008-2E4U-M	B093-008-2E4U-M
Door Monitoring Kit	SRSWITCH (Monitors Front/Rear Doors)	SRSWITCH (Monitors Front/Rear Doors)
Airflow Management	SR1UPANEL10 and/or SR1UBRUSH	SR1UPANEL10 and/or SR1UBRUSH
Cable Managers	40+ Horizontal, Vertical and External Cable Management Options at tripplite.com	
Power Cords	French/German UPS Input Cord with CEE 7/7 "Schuko" Plug (P054-006); Match Others to IT Equipment; 250+ Power Cord Options at tripplite.com	French/German UPS Input Cord with CEE 7/7 "Schuko" Plug (P050-008); Match Others to IT Equipment; 250+ Power Cord Options at tripplite.com
Network Cables	Match to IT Equipment; 1,000+ Copper and Fiber Network Cable Options at tripplite.com	
Patch Panels	60+ Copper and Fiber Patch Panel Options at tripplite.com	
Additional Sensors	E2MT (Up to 3 Sensors Total per WEBCARDLX to Monitor Top/Middle/Bottom Temperature)	

* Replaces standard PDU.

Floor-Standing Micro Data Centers (230V)

Model Summary	230V • 40U • 3 kVA	230V • 38U • 3 kVA (N+N)
Model (Validated Kit)	MDK2F40UPX00000	MDK2F38UPX00000
Model (Assembled/Tested)	MDA2F40UPX00000	MDA2F38UPX00000
Output Power Capacity	3 kVA/2.7 kW/11.7A Max	(2) 3 kVA/2.7 kW/11.7A Max (N+N Redundancy)
Rack Space	42U Total; 40U Usable	42U Total; 38U Usable
Weight Capacity	1360 kg Total; 1195 kg Usable	1360 kg Total; 1158 kg Usable
Maximum Device Depth	940 mm	940 mm
Site Power Requirements	230V, 13/16A, 50/60 Hz	(2) 230V, 13/16A, 50/60 Hz (2 Separate Circuits)
Site Outlet Required	BS 1363 (Standard) or CEE 7/7 "Schuko" (Optional)	(2) BS 1363 (Standard) or CEE 7/7 "Schuko" (Optional)
UPS Type	On-Line with Pure Sine Wave Output and Zero Transfer Time	On-Line with Pure Sine Wave Output and Zero Transfer Time
Runtime (50%/100% Load)	13.5/5 min. (Expandable)	13.5/5 min. (Expandable)
High-Availability Features	On-Line (VFI) Operation; Auto Bypass; Battery Backup; Hot-Swappable Batteries	N+N Redundancy; On-Line (VFI) Operation; Auto Bypass; Battery Backup; Hot-Swappable Batteries
PDU Type	Metered	Metered
Usable Outlets (UPS + PDU)	(40) C13, (7) C19	(80) C13, (14) C19
Dimensions (Assembled)	1994 x 600 x 1092 mm	1994 x 600 x 1092 mm
Weight (Assembled)	165 kg	202 kg
Limited Warranty	2 Years (Components Keep Longer Warranties); Extended Warranties Available	2 Years (Components Keep Longer Warranties); Extended Warranties Available
Included Hardware and Usable AC Outlets		
Rack Enclosure	SR42UB (Premium Rack; Standard Width/Depth)	SR42UB (Premium Rack; Standard Width/Depth)
UPS System	SUINTE3000LCD2U with (8) C13, (1) C19; P052-008 BS 1363 Input Cord	(2) SUINTE3000LCD2U with (16) C13, (2) C19; (2) P052-008 BS 1363 Input Cords
UPS Network Card	WEBCARDLX	(2) WEBCARDLX
Environmental Sensor	E2MTHDI (Temperature/Humidity/Digital Inputs)	E2MTHDI (Temperature/Humidity/Digital Inputs)
Standard PDU	PDUMV20HV with (32) C13, (6) C19; 0U; P036-006 Input Cord	(2) PDUMV20HV with (64) C13, (12) C19; 0U; (2) P036-006 Input Cords
Optional Accessories, Sold Separately (Visit www.tripplite.com to see the full selection.)		
Switched PDU*	PDUMV20HVNELX with (20) C13, (4) C19; 0U	(2) PDUMV20HVNELX with (40) C13, (8) C19; 0U
External Battery Packs for Extended Runtime (50%/100% Load)	40/16 min. with BP72V15-2U (Limit 1); 47/19 min. with BP72V18-2US ; 72/30 min. with BP72V28RT-3U	40/16 min. with BP72V15-2U (Limit 1); 47/19 min. with BP72V18-2US ; 72/30 min. with BP72V28RT-3U
Cooling	SRXCOOL12KB (3.5 kW; Portable; BS 1363) or SRXCOOL12K (3.5 kW; Portable; CEE 7/7 "Schuko")	SRXCOOL12KB (3.5 kW; Portable; BS 1363) or SRXCOOL12K (3.5 kW; Portable; CEE 7/7 "Schuko")
KVM Switch	B022-U16-IP ; B020-U16-19-IP (With LCD Console)	B022-U16-IP ; B020-U16-19-IP (With LCD Console)
Console Server	B093-008-2E4U-M	B093-008-2E4U-M
Door Monitoring Kit	SRSWITCH (Monitors Front/Rear Doors)	SRSWITCH (Monitors Front/Rear Doors)
Airflow Management	SR1UPANEL10 and/or SR1UBRUSH	SR1UPANEL10 and/or SR1UBRUSH
Cable Managers	40+ Horizontal, Vertical and External Cable Management Options at tripplite.com	
Power Cords	French/German UPS Input Cord(s) with CEE 7/7 "Schuko" Plug (P050-008); Match Others to IT Equipment; 250+ Power Cord Options at tripplite.com	
Network Cables	Match to IT Equipment; 1,000+ Copper and Fiber Network Cable Options at tripplite.com	
Patch Panels	60+ Copper and Fiber Patch Panel Options at tripplite.com	
Additional Sensors	E2MT (Up to 3 Sensors Total per WEBCARDLX to Monitor Top/Middle/Bottom Temperature)	

* Replaces standard PDU.

Floor-Standing Micro Data Centers (230V)

Model Summary	230V or 208/240V • 38U • 6 kVA	230V or 208/240V • 34U • 6 kVA (N+N)
Model (Validated Kit)	MDK3F38UPX00000	MDK3F34UPX00000
Model (Assembled/Tested)	MDA3F38UPX00000	MDA3F34UPX00000
Output Power Capacity	6 kVA/5.4 kW/23.5A Max (230V)	(2) 6 kVA/5.4 kW/23.5A Max (230V) (N+N Redundancy)
Rack Space	42U Total; 38U Usable	42U Total; 34U Usable
Weight Capacity	1360 kg Total; 1171 kg Usable	1360 kg Total; 1116 kg Usable
Maximum Device Depth	940 mm	940 mm
Site Power Requirements	230V, 32A or 208/240V, 30A, 50/60 Hz	(2) 230V, 32A or 208/240V, 30A, 50/60 Hz (2 Separate Circuits)
Site Wiring Required	Hardwire (230V 32A L-N-G or 208/240V 30A L1-L2-G)	(2) Hardwire (230V 32A L-N-G or 208/240V 30A L1-L2-G)
UPS Type	On-Line with Pure Sine Wave Output and Zero Transfer Time	On-Line with Pure Sine Wave Output and Zero Transfer Time
Runtime (50%/100% Load)	8.5/2 min. (Expandable)	8.5/2 min. (Expandable)
High-Availability Features	On-Line (VFI) Operation; Auto Bypass; Battery Backup; Hot-Swappable Batteries; Hot-Swappable Power Module	N+N Redundancy; On-Line (VFI) Operation; Auto Bypass; Battery Backup; Hot-Swappable Batteries; Hot-Swappable Power Modules
PDU Type	Metered	Metered
Usable Outlets (UPS + PDU)	(64) C13, (14) C19	(64) C13, (18) C19
Dimensions (Assembled)	1994 x 600 x 1092 mm	1994 x 600 x 1092 mm
Weight (Assembled)	189 kg	244 kg
Limited Warranty	2 Years (Components Keep Longer Warranties); Extended Warranties Available	2 Years (Components Keep Longer Warranties); Extended Warranties Available
Included Hardware and Usable AC Outlets		
Rack Enclosure	SR42UB (Premium Rack; Standard Width/Depth)	SR42UB (Premium Rack; Standard Width/Depth)
UPS System	SU6000RT4UHV G with (2) C19	(2) SU6000RT4UHV G with (6) C19
UPS Network Card	WEBCARDLX	(2) WEBCARDLX
Environmental Sensor	E2MTHDI (Temperature/Humidity/Digital Inputs)	E2MTHDI (Temperature/Humidity/Digital Inputs)
Standard PDU	(2) PDUMV20HV with (64) C13, (12) C19; (2) P036-006 Input Cords	(2) PDUMV20HV with (64) C13, (12) C19; (2) P036-006 Input Cords
Optional Accessories, Sold Separately (Visit www.tripplite.com to see the full selection.)		
Switched PDU*	(2) PDUMV20HVNETLX with (40) C13, (8) C19; 0U	(2) PDUMV20HVNETLX with (40) C13, (8) C19; 0U
External Battery Packs for Extended Runtime (50%/100% Load)	22/8.5 min. with BP192V5RT2U (Limit 1); 42/17 min. with BP192V12-3U	22/8.5 min. with (2) BP192V5RT2U (Limit 1 per UPS); 42/17 min. with (2) BP192V12-3U
Cooling	SRCOOL7KRM (2 kW; 8U Rack-Mount, NEMA 5-15P) or SRCOOL12K (3.5 kW; Portable; NEMA 5-15P)	SRCOOL7KRM (2 kW; 8U Rack-Mount, NEMA 5-15P) or SRCOOL12K (3.5 kW; Portable; NEMA 5-15P)
KVM Switch	B022-U16-IP ; B020-U16-19-IP (With LCD Console)	B022-U16-IP ; B020-U16-19-IP (With LCD Console)
Console Server	B093-008-2E4U-M	B093-008-2E4U-M
Door Monitoring Kit	SRSWITCH (Monitors Front/Rear Doors)	SRSWITCH (Monitors Front/Rear Doors)
Airflow Management	SR1UPANEL10 and/or SR1UBRUSH	SR1UPANEL10 and/or SR1UBRUSH
Cable Managers	40+ Horizontal, Vertical and External Cable Management Options at tripplite.com	
Power Cords	Match to IT Equipment; 250+ Power Cord Options at tripplite.com	
Network Cables	Match to IT Equipment; 1,000+ Copper and Fiber Network Cable Options at tripplite.com	
Patch Panels	60+ Copper and Fiber Patch Panel Options at tripplite.com	
Additional Sensors	E2MT (Up to 3 Sensors Total per WEBCARDLX to Monitor Top/Middle/Bottom Temperature)	

* Replaces standard PDU.

Floor-Standing Micro Data Centers (230V)

Model Summary	230V or 208/240V • 36U • 10 kVA	230V or 208/240V • 30U • 10 kVA (N+N)
Model (Validated Kit)	MDK3F36UPX00000	MDK3F30UPX00000
Model (Assembled/Tested)	MDA3F36UPX00000	MDA3F30UPX00000
Output Power Capacity	10 kVA/9 kW/39.1A Max (230V)	(2) 10 kVA/9 kW/39.1A Max (230V) (N+N Redundancy)
Rack Space	42U Total; 36U Usable	42U Total; 30U Usable
Weight Capacity	1360 kg Total; 1126 kg Usable	1360 kg Total; 1025 kg Usable
Maximum Device Depth	37 in. (940 mm)	37 in. (940 mm)
Site Power Requirements	230V, 63A or 208/240V, 60A, 50/60 Hz	(2) 230V, 63A or 208/240V, 60A, 50/60 Hz (2 Separate Circuits)
Site Wiring Required	Hardwire (230V 63A L-N-G or 208/240V 60A L1-L2-G)	(2) Hardwire (230V 63A L-N-G or 208/240V 60A L1-L2-G)
UPS Type	On-Line with Pure Sine Wave Output and Zero Transfer Time	On-Line with Pure Sine Wave Output and Zero Transfer Time
Runtime (50%/100% Load)	12/4.3 min. (Expandable)	12/4.3 min. (Expandable)
High-Availability Features	On-Line (VFI) Operation; Auto Bypass; Battery Backup; Hot-Swappable Batteries; Hot-Swappable Power Module	N+N Redundancy; On-Line (VFI) Operation; Auto Bypass; Battery Backup; Hot-Swappable Batteries; Hot-Swappable Power Modules
PDU Type	Metered	Metered
Usable Outlets (UPS + PDU)	(64) C13, (16) C19	(64) C13, (22) C19
Dimensions (Assembled)	1994 x 600 x 1092 mm	1994 x 600 x 1092 mm
Weight (Assembled)	234 kg	335 kg
Limited Warranty	2 Years (Components Keep Longer Warranties); Extended Warranties Available	2 Years (Components Keep Longer Warranties); Extended Warranties Available
Included Hardware and Usable AC Outlets		
Rack Enclosure	SR42UB (Premium Rack; Standard Width/Depth)	SR42UB (Premium Rack; Standard Width/Depth)
UPS System	SU10000RT3UG with (4) C19	(2) SU10000RT3UG with (10) C19
UPS Network Card	WEBCARDLX	(2) WEBCARDLX
Environmental Sensor	E2MTHDI (Temperature/Humidity/Digital Inputs)	E2MTHDI (Temperature/Humidity/Digital Inputs)
Standard PDU	(2) PDUMV20HV with (64) C13, (12) C19; (2) P036-006 Input Cords	(2) PDUMV20HV with (64) C13, (12) C19; (2) P036-006 Input Cords
Optional Accessories, Sold Separately (Visit www.tripplite.com to see the full selection.)		
Switched PDU*	(2) PDUMV20HVNETLX with (40) C13, (8) C19; 0U	(2) PDUMV20HVNETLX with (40) C13, (8) C19; 0U
External Battery Packs for Extended Runtime (50%/100% Load)	29/12 min. with BP240V10RT3U ; 49/20 min. with (2) BP240V10RT3U	29/12 min. with (2) BP240V10RT3U ; 49/20 min. with (4) BP240V10RT3U
Cooling	SRCOOL7KRM (2 kW; 8U Rack-Mount, NEMA 5-15P) or SRCOOL12K (3.5 kW; Portable; NEMA 5-15P)	SRCOOL7KRM (2 kW; 8U Rack-Mount, NEMA 5-15P) or SRCOOL12K (3.5 kW; Portable; NEMA 5-15P)
KVM Switch	B022-U16-IP ; B020-U16-19-IP (With LCD Console)	B022-U16-IP ; B020-U16-19-IP (With LCD Console)
Console Server	B093-008-2E4U-M	B093-008-2E4U-M
Door Monitoring Kit	SRSWITCH (Monitors Front/Rear Doors)	SRSWITCH (Monitors Front/Rear Doors)
Airflow Management	SR1UPANEL10 and/or SR1UBRUSH	SR1UPANEL10 and/or SR1UBRUSH
Cable Managers	40+ Horizontal, Vertical and External Cable Management Options at tripplite.com	
Power Cords	Match to IT Equipment; 250+ Power Cord Options at tripplite.com	
Network Cables	Match to IT Equipment; 1,000+ Copper and Fiber Network Cable Options at tripplite.com	
Patch Panels	60+ Copper and Fiber Patch Panel Options at tripplite.com	
Additional Sensors	E2MT (Up to 3 Sensors Total per WEBCARDLX to Monitor Top/Middle/Bottom Temperature)	

* Replaces standard PDU.

Distributed By:



Pulse Supply
909 Ridgebrook Road., Sparks, Maryland 21152, USA
TEL : +1-410-583-1701 FAX : +1-410-583-1704
E-mail: sales@pulsesupply.com
<https://www.pulsesupply.com/tripp-lite>

