

## ErisTerminal® SIP DECT Base Station

### VSP600-B

Add hands-free mobility to your SIP communications with the VSP600-B base station. Thanks to DECT 6.0 technology, you can add up to six cordless devices per base station, using any combination of our VSP601 SIP cordless handsets or VSP608 SIP cordless desksets each with its own extension or unique phone number. The base station can be configured for up to six lines and supports up to four active, concurrent calls.



### VSP600-B Key Features

#### **Super-clear mobility with Orbitlink Wireless Technology**

Leave your desk without leaving your work behind and enjoy DECT 6.0 sound quality and reception.

#### **Scalability**

Growing pains? Register up to six cordless handsets and/or desksets to the VSP600-B DECT cordless base station and program each one with its own phone number or extension.

#### **Advanced call handling**

Impress customers with comprehensive call handling features that are compatible with hosted and open-source PBX platforms.\*

#### **Simultaneous call handling**

View and manage up to two calls at the same time (per handset). Calls are displayed on screen, making them easy to answer, transfer, forward, etc.

#### **Flexibility**

With support for up to six SIP lines/accounts, you can manage multiple calls with advanced call handling features.

#### **Intuitive design**

You're in business with a user-friendly interface, large backlit display, two soft keys and navigational pad.

#### **Convenient mounting**

Make the most of tight spaces. The VSP600-B DECT cordless base station can be free standing or wall-mounted.

#### **Three-year warranty**

Enjoy the peace of mind that comes with an industry-leading, standard three-year warranty. VTech also provides advanced replacement on warranty claims using new, not refurbished products.



Pulse Supply  
909 Ridgebrook Road.  
Sparks, Maryland 21152, USA

TEL : +1-410-583-1701  
FAX : +1-410-583-1704  
E-mail: [sales@pulsesupply.com](mailto:sales@pulsesupply.com)  
<https://www.pulsesupply.com/vtech>

\*Compatible with Broadsoft®, Genband®, Metaswitch Networks and Asterisk-based platforms.



## Specifications, Weights and Dimensions

- Color: Black
- UPC: 735078040343
- Product dimensions (WxDxH): 4.55" x 1.67" x 5.94"
- Product weight: 0.73 lbs
- Giftbox dimensions (WxDxH): 4.88" x 2.83" x 6.14"
- Giftbox weight: 0.86 lbs.
- Master pack dimensions (WxDxH): 10.47" x 6.26" x 6.93"
- Master pack weight: 3.97 lbs.
- Quantity: 4

## Interface

- DECT 6.0 RF module embedded
- DECT 6.0 (maximum register): 6 handsets and/or desksets
- Ethernet port - 10/100MB
- Base power: adapter (included) and Class 2 Power over Ethernet (PoE)

## Base Station Keys and Indicators

- Handset locator key
- Reset key
- Power LED
- VoIP LED

## System Features

- Supports up to 6 SIP account registrations (individual or shared among handsets)
- Supports up to 4 outgoing calls in parallel (system-wide)
- Base phonebook up to 200 entries
- Phonebook import/export
- LDAP remote phonebook
- Call history up to 200 entries
- Do Not Disturb (DND)
- 3-way local conference
- N-way network conference
- External/Internal call transfer between handsets
- Call barring/blocking (block anonymous/blacklist)
- Dial plan/digit map
- Intercom
- Mute
- Redial
- 10 speed dial entries
- Call transfer: blind/attended
- Call hold
- Call forwarding: per-line basis (busy/always/no answer)

- Call timer (call duration)
- Caller ID
- Phonebook matching (incoming and outgoing calls)
- Multi-language support

## Customization

- Web interface configuration (admin & user)
- Custom default file

## Security

- 802.1x
- 802.1pq
- Transport Layer Security (TLS)
- AES encryption of config file for provisioning (128/64/32/16 bits)
- LLDP-MED

## Network

- STUN
- NAT
- RTP, SRTP
- SNTP
- VLAN
- Failover support and server redundancy
- Layer 3 QoS (ToS, Diffserv)

## Voice Codec

- G.711 a-law & u-law
- G.722
- G.726
- G.729

## Provisioning

- HTTP, HTTPS, FTP, TFTP
- DHCP options: 66, 159,160
- PnP

## Maintenance

- Diagnostic: pcap trace
- Schedule Resync – time and day setting
- Software Update Over the Air (SUOTA)
- Syslog

## Compatibility

- Broadsoft® Broadworks®
- Asterisk-based platforms
- Metaswitch Networks
- Genband™

## Other

- 3-year standard warranty
- Advanced product replacement for warranty claims with new product



Pulse Supply  
909 Ridgebrook Road.  
Sparks, Maryland 21152, USA

TEL : +1-410-583-1701  
FAX : +1-410-583-1704  
E-mail: sales@pulsesupply.com  
<https://www.pulsesupply.com/vtech>